


High pressure solenoid valve manifold

Further customized solutions available upon request



Technical features

Medium:

For compressed natural gas (CNG)

Switching function:

Normally closed

Operation:

Indirectly solenoid actuated

Mounting position:

Optional, preferably with filter on the bottom side

Flow direction:

Determined

Port size:

G1/2

Operating pressure:

10 ... 320 bar

Leakage:

Internal Leakage acc. to DIN EN 12266-1 Leakage "C"
External Leakage acc. to DIN EN 12266-1 Leakage "A"

Fluid temperature:

-20 ... +60°C

Ambient temperature:

-20 ... +50°C

Material:

Body: Brass
Seat seal: Polymer
Internal parts: Brass, Stainless steel, Polymer

Technical data - standard models

Consisting of:	Port size	Nominal Diameter (mm)	Operating pressure (max. Differential pressure) (bar)	Weight (kg)	Model Solenoid in V d.c./a.c.
<ul style="list-style-type: none"> - 3 solenoid valves to control the filling of the Low-, Middle- and High-Bank - 3 solenoid valves to control a dispenser with one line - 1 solenoid valve as security valve in front of the dispenser - 6 non return valves to avoid the inflow from higher pressure levels (e. g. High Bank) to lower pressure levels (e. g. Middle Bank) - 2 additional non return valves for filling a car directly from the compressor via the dispenser (without needing to pre-fill the banks), necessary at highly frequented stations - 3 filters 40 µm 	G1/2	8	10 ... 320	40	8590631.9841.xxxxx

xxxxx Please insert voltage and frequency codes

Acc. to PED 97/23/EC and ATEX 94/9/EC!

Option selector

8590★★★★★★★★

Port size	Substitute
1/2	631

Frequency	Substitute
See table frequency codes	xx
Voltage	Substitute
See Voltage Codes	xxx
Solenoid options	Substitute
Solenoid with 10 m cable ends Protection class according to - II 2 G Ex mb IIC T4 Gb - II 2 D Ex mb tb IIIC T130°C Db	9845
For d.c. with 1/2 - 14 NPT female thread and 460 mm flying leads Protection class acc. to ANSI/NEMA USA: FM approved (File-No. 2Z2A6.AE) Canada: CSA certified (File-No. LR 57643-6) Solenoids in temperature class T3C (160°C) are useable in Ex-areas (see table Ex-areas)	3826
For a.c. with integrated rectifier with 1/2 - 14 NPT female thread and 460 mm flying leads Protection class acc. to ANSI/NEMA USA: FM approved (File-No. 2Z2A6.AE) Canada: CSA certified (File-No. LR 57643-6) Solenoids in temperature class T3C (160°C) are useable in Ex-areas (see table Ex-areas)	3827
Solenoid with terminal box cable gland M20 x 1,5 cable clamp ø 5 ... 8 mm Protection class according to - II 2 G Ex e mb IIC T4/T5 Gb - II 2 D Ex tb IIIC T 130°C Db IP66 Ambient temperature: T4 -40 ... +50°C T5 -40 ... +40°C	428x
Solenoid with terminal box cable gland M20 x 1,5 (cable clamp ø 10 ... 14 mm) 1/2 ... 1/4 NPT (cable clamp ø 7,5 ... 11,9 mm) Protection class according to - II 2 G Ex d mb IIC T4/T5 Gb - II 2 D Ex tb IIIC T 130°C Ambient temperature: T4 -40 ... +50°C T5 -40 ... +40°C	468x

Standard solenoid systems

Voltage and Frequency Solenoid 9841					
Code	Code	Voltage	Frequency	Power consumption	
Voltage	Frequency			Inrush	Holding
024	00	24 V d.c.	-	10,1 W	10,1 W
230	59	230 V a.c.	50 ... 60 Hz	9,2 VA	9,2 VA

Solenoid systems

ATEX category	Protection class	Solenoid	Standard voltages
II2GD	Ex mb IIC T4 Gb Ex mb tb IIIC T 130°C Db with 3 m connection cable	9841	24 V d.c., 110 V a.c., 230 V a.c.

Ex-areas

	Class	Division	Groups
Gases + fumes	I	1 and 2	A ... D
Dusts	II	1 and 2	E ... G
Fibres + fluffs	III	1 and 2	-

Electrical details for all solenoid systems

Voltage range	±10%
Duty cycle	100% ED
Protection class	EN 60529 IP65

According to DIN VDE 0580 at a solenoid temperature of +20°C. At operating state temperature the input power of a coil decreases by up to ca. 30% due to physical reasons.

Dimensions

